



## केन्द्रीय मुहर विभाग - III

हमारा संदर्भ- केन्द्रीय मुहर विभाग-३/१६: भा.मा. 2347

21 जनवरी 2026

विषय: अनुपालन हेतु गाइडलाइन

सभी शाखा कार्यालयों से आग्रह है कि संलग्न गाइडलाइन का अनुपालन तत्काल प्रभाव से सुनिश्चित करें।

(राकेश कुमार)  
वैज्ञानिक 'ई' /निदेशक (के मु वि III)

### प्रमुख (के मु वि III)

सभी क्षेत्रीय/शाखा कार्यालय

## CENTRAL MARKS DEPARTMENT-III

Our Ref: **CMD-3/16: IS 2347**

**21 January 2026**

**Subject: Guidelines for implementation of Amendment No. 3 to Indian Standard IS 2347: 2023- Domestic Pressure Cookers**

This has reference to the subject mentioned above.

BOs may kindly ensure implementation of the attached guidelines with immediate effect.

(Rakesh Kumar)  
Scientist 'E'/Director (CMD III)

### Head (CMD - III)

Circulated to: All ROs/BOs

### **CENTRAL MARKS DEPARTMENT-III**

Our Ref: **CMD-3/16: IS 2347**

**21 January 2026**

**Subject: Guidelines for implementation of Amendment No. 3 to Indian Standard IS 2347: 2023- Domestic Pressure Cookers**

1. Amendment No. 3 to IS 2347: 2023 has been published. **The last date for implementation of the Amendment is 19 May 2026.**
2. All BOs shall inform the Applicants and Licensees under their jurisdiction about implementation of the Amendment **within a week of issuance of these guidelines.**
3. The significant changes brought through this Amendment as listed in the Table below is given for the purpose of general guidance. BOs shall ensure that the product conforms to all the requirements, as applicable, of the Standard read along with its Amendments.

<b>Sl. No.</b>	<b>Page No, Clause reference</b>	<b>Change</b>
1.	Page 3, clause 5.5- Material of Pressure Regulating device	It has been specified that sleeve of PRD can also be made from heat insulating material like glass filled nylon (Nylon 6 or Nylon 66). Supplier Certificate is acceptable in case of heat insulating material like glass filled nylon is used.
2.	Page 5, clause 8.3.1- Operating test of PRD	It has now been specified that the drop in the pressure after operation of the PRD shall not be more than 50 percent ( <i>in place of 40 % specified earlier</i> ) of the average measured cooking steam pressure when PRD operates.,

4. No changes in manufacturing or testing facilities are required, neither any test report nor documentary evidence are required for implementation of the Amendment.
5. Consequent upon issuance of the Amendment, existing Product Manual has also been revised as Doc: PM/ IS 2347/11/ January 2026. In this revision, changes have been made in requirements of Scheme of Inspection and Testing. .
6. The above guidelines come into force with immediate effect.

**(Rakesh Kumar)**  
**Scientist 'E'/Director (CMD III)**

**Head (CMD III)**

**DDG (Certification)**