

BUREAU OF INDIAN STANDARDS
DRAFT FOR COMMENTS ONLY

(Not to be reproduced without the permission of BIS or used as an Indian Standard)

मसौदा संशोधन सं. 1

आई एस 3652 : 2024 फसल संरक्षण उपकरण – रॉकर फुहारा – विशिष्ट और परीक्षण संहिता
(पांचवां पुनरीक्षण)

Draft **AMMENDMENT NO. 1 to**

IS 3062 : 2024 CROP PROTECTION EQUIPMENT — ROCKER SPRAYER —
SPECIFICATION AND TEST CODE (Fifth Revision)

Agricultural Machinery and Equipment Sectional Committee, FAD 11	Last date for Comments: 1 November 2025
---	--

[Page 15, Annex D, clause **D-7.2.2**, Para 2] — Substitute ‘The test liquid shall be changed after every 6 hours of use.’ For ‘The test liquid shall be changed after every 6 months of use.’

[Page 19, Annex F, clause **F-2.4**] — Substitute ‘The total length or the spray gun when measured from the top or the nozzle to the tip of the trigger or screw shall be not less than 500 mm.’ for ‘The total length or the spray gun when measured from the top or the nozzle to the tip of the trigger or screw shall be less than 500 mm.’

[Page 22, Annex G, clause **G-2.1.2**, line 5] — Substitute ‘The hole in nozzle is either rectangular or more commonly lenticular in shape’ for ‘The hole in nozzle is either rectangular or more commonly ventricular in shape’

[Page 27, Annex G, clause **G-7.2**, sentence 1] — Substitute the following for existing:

‘Turn on the supply and adjust the pressure and direct the spray, for a period timed by stopwatch, into receiving vessel so designed as to collect the whole of the spray from the nozzle.’

[Page 27, Annex G, clause **G-8.1.1**] — Substitute the following for existing:

‘The patternator (see Fig. 20) normally consist of 16 channels each 25 ± 0.25 mm wide and of any convenient length provided that it encompasses the area of the spray. The number of channels may be increased or decreased so that the whole of the spray falls within the patternator. The channels lead the liquid directly to the measuring tube having a bore not more than 24 mm and be long enough to hold minimum of 200 ml test liquid. The depth of channels shall be at least 100 mm to avoid rebound of the spray droplets. The top edge of the trough dividers shall be sharp (tapered to not more than 0.25 mm width on the top edge) and straight in the horizontal plane, so that no point along with the edge lies more than 1 mm from the straight line joining the corresponding point at each end. The top edges of the dividers shall be positioned so that when a straight edge is laid across the full width of the front and back of the troughs no edge lies more than 1 mm below this. Each divider shall be straight in the vertical plane to within ± 0.25 mm.

NOTE — The surface of patternator should be such that the droplets should not stick on it.’

[Page 27, Annex G, clause **G-8.2.2**, line 2] — Insert ‘at’ after ‘spray sheet is’.

[Page 31, Annex G, clause **G-10.1.1**, Table, S.No. iii), col 3] — Substitute ‘ $0.022 \mu\text{m}$ ’ for ‘ $0.0022 \mu\text{m}$ ’