

Wide Circulation Draft

भारतीय मानक ब्यूरो

BUREAU OF INDIAN STANDARDS

Draft for comments only

Doc No.: TXD 33 (28746)

September 2025

(Not to be reproduced without permission of BIS or used as Standard)

भारतीय मानक मसौदा

बिना बुने हुए वस्त्रादि – परीक्षण विधि – भाग 6 : अवशोषण

(आईएस 15891 भाग 6/आईएसओ 9073 भाग 6 का पहला पुनरीक्षण)

Draft Indian Standard

Nonwovens — Test methods — Part 6: Absorption

(First Revision of IS 15891 part 6/ISO 9073 part 6)

ICS: 59.080.30

Industrial Fabrics
Sectional Committee, TXD 33

Last date for receipt of comments is
25 October 2025

NATIONAL FOREWORD

(Formal clauses will be added later)

This Indian Standard intended to be adopted is identical with ISO 9073-6 : 2025 ‘Nonwovens — Test methods Part 6: Absorption’ issued by the International Organization for Standardization (ISO).

This standard was originally published in 2012 which was identical with ISO 9073-6 : 2000. The first revision of this standard has been undertaken to harmonize it with the latest version of ISO 9073-6 : 2025.

This standard has been published in various parts. Other parts in this series are:

Part 1 Determination of mass per unit area

Part 2 Determination of thickness

Part 3 Determination of tensile strength and elongation at break using the strip method

Part 4 Determination of tear resistance by the trapezoid procedure

Part 5 Determination of resistance to mechanical penetration (ball burst procedure)

Part 7 Determination of bending length

Part 8 Determination of liquid strike-through time (simulated urine) for nonwoven coverstocks

Part 9 Determination of drapability including drape coefficient
Part 10 Lint and other particles generation in the dry state
Part 11 Run-off
Part 12 Demand absorbency
Part 13 Repeated liquid strike-through time (simulated urine)
Part 14 Coverstock wetback (simulated urine)
Part 15 Determination of air permeability
Part 16 Determination of resistance to penetration by water (hydrostatic pressure)
Part 17 Determination of water penetration (spray impact)
Part 18 Determination of tensile strength and elongation at break using the grab tensile test

The text of ISO Standard has been approved as suitable for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words ‘International Standard’ appear referring to this standard, they should be read as ‘Indian Standard’.
- b) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a point (.) as the decimal marker.

In the standard intended to be adopted, reference appears to certain International Standard for which Indian Standard also exist. The corresponding Indian Standards which are to be substituted in their respective places are listed below along with their degree of equivalence for the edition indicated:

<i>International Standard</i>	<i>Corresponding Indian Standard</i>	<i>Degree of Equivalence</i>
ISO 139 Textiles — Standard atmospheres for conditioning and testing	IS 6359 : 2023 Method for conditioning of textiles (<i>first revision</i>)	Technically Equivalent
ISO 186 Paper and board — Sampling to determine average quality	IS 1060 (Part 5/Sec 1): 2014 ISO 186: 2002 Methods of sampling and test for paper and allied products Part 5 Methods of test for paper and board Section 1 Sampling to determine average quality	Identical
ISO 565 Test sieves — Metal wire cloth, perforated metal plate and electroformed sheet — Nominal sizes of openings	IS 460 (Part 1): 2020 Test sieves — Specification Part 1 Wire cloth test sieves (<i>fourth revision</i>) IS 460 (Part 2): 2020	Technically Equivalent

	Test sieves — Specification Part 2 Perforated plate test sieves (<i>fourth revision</i>)	
--	---	--

The conditioning temperature of $20 \pm 2^{\circ}\text{C}$ as specified in International Standards is not suitable for tropical countries like India where the atmospheric temperature is normally much higher than 20°C . It is almost impossible to maintain this temperature specially during summer when the atmospheric temperature rises even up to 50°C . In view of the above, IS 6359 : 2023 Method for conditioning of textiles (*first revision*) which specifies a temperature of $27 \pm 2^{\circ}\text{C}$ for conditioning of the test specimens for the tropical countries like India shall be referred.

In reporting the result of a test or analysis made in accordance with this standard, if the final value; observed or calculated, is to be rounded off, it shall be done in accordance with IS 2: 2022 'Rules for rounding off numerical values (*second revision*).

Extract of ISO 9073-6 : 2025 'Nonwovens — Test methods — Part 6: Absorption

1 SCOPE

This document specifies methods for the evaluation of some aspects of the behaviour of nonwoven fabrics in the presence of liquids. In particular:

- i) The liquid absorbency time;
- ii) The liquid absorptive capacity;
- iii) The liquid wicking rate (capillarity).

The different aspects of absorbency can relate to various end uses of the tested products.

The tests do not apply to any fabric containing super absorbent materials.

2 NORMATIVE REFERENCES

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

- i) ISO 139 Textiles — Standard atmospheres for conditioning and testing
- ii) ISO 186 Paper and board — Sampling to determine average quality
- iii) ISO 565 Test sieves — Metal wire cloth, perforated metal plate and electroformed sheet
— Nominal sizes of openings

3 TERMS AND DEFINITIONS

For the purposes of this document, the following terms and definitions apply.

3.1 Liquid Absorbency Time

time required for a sample of absorbent material to become completely wetted by the test liquid

Note 1 to entry: I.e. to imbibe a liquid into its interior structure under specified conditions.

3.2 Liquid Absorptive Capacity

LAC

mass of liquid that is absorbed by unit mass of the test absorbent expressed as a percentage of the mass of the test absorbent, under specified conditions and after a specified time

3.3 Liquid Wicking Rate

measure of the capillarity of the test material

Note 1 to entry: I.e. the rate at which the liquid is transported into the fabric by capillary action.

FORMAT FOR SENDING COMMENTS ON BIS DOCUMENTS

(Please use A4 size sheet of paper only and type within fields indicated. Comments on each clause/sub clause/table/fig etc. be started on a fresh box. Information in column 3 should include reasons for the comments and suggestions for modified working of the clauses when the existing text is found not acceptable. Adherence to this format facilitates Secretariat's work)

Please e-mail your comments to txd@bis.gov.in or faxed on 011-23231282.

NAME OF THE COMMENTATOR/ORGANIZATION:

DOCUMENT NO:

BIS LETTER REFERENCE NO.:

Item, Clause Sub-Clause No. Commented upon (Use Separate Box afresh)	Comments	Specific Proposal (Draft clause to be add/amended)	Remarks	Technical References and justification on which (2), (3), (4) are based
(1)	(2)	(3)	(4)	(5)