

Indian Standard
SPECIFICATION FOR
HANDLOOM BUCKRAM CLOTH

0. FOREWORD

0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 27 May 1968, after the draft finalized by the Handloom and Khadi Sectional Committee had been approved by the Textile Division Council.

0.2 This standard, first published in 1957, prescribed the constructional details and other particulars of only one variety of handloom buckram cloth. The Sectional Committee decided that the standard be revised in order to include additional varieties of buckram cloth which are currently manufactured. This opportunity has also been availed of to make certain modifications in regard to the requirements of the cloth.

0.3 Buckram cloth is generally used for interlining of garments to give stiffness.

0.4 This standard contains clauses which call for agreement between the purchaser and the supplier/which permit the purchaser to use his option for selection to suit his requirements. The relevant clauses are **2.2.3, 2.2.4, 4.1.1, 6.1** and **7.3**, length and width of cloth (*see* Table 1) and value of the scouring loss (*see* Table 2).

0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the constructional details and other particulars of four varieties of handloom buckram cloth.

*Rules for rounding off numerical values (*revised*).